

**Technical Data Sheet**  
Edition 1, 2004  
Identification no.  
02 01 03 02 000 0 000091  
Version no. 0010  
Sika Separol 10

# Sika Separol 10

## Chemical Form Release Agent

**Description** Form release agent

**Uses** Form release agent for steel and wooden formwork. Sika Separol 10 facilitates removal and cleaning of shuttering. Number of lifts is substantially increased.

**Advantages**

- Ready-to-use
- Easy to apply
- Combined chemical and physical action
- Ensures fair faced concrete finish
- No staining

Suitable also for use on formwork used in steam curing process

### Technical Data

**Form/ Colour** Liquid / Reddish

**Density** ~ 0.84 kg/ltr

**Coverage**

- On timber / plywood formwork, 1 ltr. for approx. 20 - 25 m<sup>2</sup>
- On metal or plastic formwork 1 ltr. for approx. 40 m<sup>2</sup>.

**Storage** Dry, cool, shaded place (max. +30 °C).

**Shelf life** Min. 24 months if stored properly in unopened, original packaging

**Packaging** 200 ltr drum  
Bulk container

### Application

**Surface preparation** All surfaces to be coated with Sika Separol 10 must be clean and free from grease and old concrete.

**Application** Apply one uniform, thin coat of Sika Separol 10 by brush, roller or spray equipment, on dry or damp formwork.  
To achieve optimum result it is recommended to pour the concrete minimum 4 hours after Sika Separol 10 application.

**Cleaning** Clean all tools and equipment with solvent.

**Remarks** Protect fresh coat from rain.  
Cleaning the mould surface between each use and before application is essential to prevent the formation of hardened concrete "build up".

**Precautionary measures** Sika Separol 10 contains flammable materials and falls under the dangerous goods regulations (class 3).

During application in confined areas, ditches, shafts etc. adequate ventilation must be provided. During its application open fire and other igniting agents (e.g. welding works) must be removed.

Wear suitable protective clothing, goggles and gloves during working with this product.

In a liquid not fully cured state the thinner and the product contaminate water and should not get into drains, water and ground.



Table of Contents

## Legal Notes

The information and in particular the recommendations relating to the application and end-use of Sika products are given in good faith based on Sika's current knowledge and experience of the product when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sales and delivery. Users should always refer to the most recent issue of the technical Data Sheet for the product concerned, copies of which will be supplied on request.



**PT. Sika Indonesia**  
Jl. Raya Cibinong-Bekasi km. 20  
Limusnunggal- Cileungsi  
BOGOR 16820 - Indonesia  
Tel. +62 21 8230025  
Fax +62 21 8230026  
Website : [www.sika.co.id](http://www.sika.co.id)  
e-mail: [sikacare@id.sika.com](mailto:sikacare@id.sika.com)

**Branches**  
Surabaya :  
Puri Niaga Blok G No. 29, Jl. Raya Rungkut Menanggal 11, Surabaya  
Tel : 031-8690202 ; Fax : 031-8682123  
Medan :  
Jl. Pancing / Jl. Willem Iskandar No.75 & 75 A, Kec. Medan Tembung  
Tel : 061- 6619500; Fax : (061) 6619400  
Batam :  
Jl. Laksamana Bintan, Komp. Bumi Riau Makmur Blok E No.3, Sungai Panas  
Tel : (0778) 424928; Fax : (0778) 450189

